

NAME

fmtutil.cnf – configuration file for fmtutil

DESCRIPTION

The *fmtutil.cnf* file contains the configuration information for **fmtutil**(8). Each line contains the name of the format (e.g., “*tex*”, “*latex*”, “*omega*”), the name of the engine that is used by that format (e.g., “*tex*”, “*etex*”, “*omega*”), the pattern file (e.g., *language.dat*, *language.def*), and any arguments (name of an *.ini* file).

Fields are separated by whitespace and complete lines can be commented out with “#”. The “pattern file” field cannot be used to define a file that is used while building the format. It tells **fmtutil** which files (separated by commas) the format creation procedure reads and it has an effect to the options *--showhyphen* and *--byhyphen*. If the format has no way to customize hyphenation, a “-” can be used to indicate this.

NOTES

The **tex**(1) and **amstex**(1) formats always load *hyphen.tex*. No customization by a pattern file is available for these formats. Therefore, the pattern-file field for the **tex** and **amstex** is usually indicated to be empty (“-”).

You can, however, build customized formats on top of plain **tex**(1) or **amstex**(1) by using *bplain.tex* instead of *plain.tex* (b for the *Babel* system). See, for example, the *bplain.ini* file for the bplain format).

etex(1) loads *language.def*, not *language.dat*.

Symbolic links to the correct engines (e.g., *bplain -> tex*) are generated by the **texlinks**(8) script. Remember to run **texlinks**(8) if you run **fmtutil**(8) yourself, rather than using the **FORMATS** option in **texconfig**(8).

FILES

fmtutil.cnf
default configuration file

language.dat
hyphenation pattern file

language.def
hyphenation pattern file

language.dat.lua
hyphenation pattern file

SEE ALSO

amstex(1), **etex**(1), **fmtutil**(8), **tex**(1), **texconfig**(8), **texlinks**(8).

Web page: <<http://tug.org/teTeX/>>

BUGS

None known, but report any bugs found to <tetex@db.s.uni-hannover.de> (mailing list).

AUTHOR

fmtutil.cnf was written by Thomas Esser <te@db.s.uni-hannover.de>, and is Copyright 1998, 1999 but released into the public domain.

This manual page was written by C.M. Connelly <c@eskimo.com>, for the Debian GNU/Linux system. It may be used by other distributions without contacting the author. Any mistakes or

omissions in the manual page are my fault; inquiries about or corrections to this manual page should be directed to me (and not to the primary author).