

photobook — Document class for building photo-books *

Alex A. Naanou[†]

Released 2022-11-14

Abstract

The `photobook` L^AT_EX document class extends the `book` class defining a set of parameters, meta-macros, macros and environments with reasonable defaults to help typeset, build and print books mainly based on visual/image content.

Contents

Introduction	2	Paper cells	13
Usage	2	Page cells	13
Options	2	Foldout page cells	14
Page geometry	2	Multi-page cells	17
layout	3	Endpaper cells	17
Image clearance	4	Cover and dust jacket cells	18
Image block layout	4	Caption Templates	18
PDF Viewer layout	5	Page Templates	18
Other options	5	Tweaking	18
Packages	5	General interface	19
Globals	5	No bleed	19
Initialization	6	Partial bleed	21
Generic commands	7	Full bleed	22
Environments and Cells	7	Spread Templates	23
Generic	7	No bleed	23
Cells	7	Partial bleed	24
Save cells	9	Full bleed	25
Cell macros	9	Meta Macros / Environments	25
		Miscellaneous	26

*This file describes version v0.1.5, last revised 2022-11-14.

[†]E-mail: alex.nanou@gmail.com

Introduction

L^AT_EX is great with textual and text-primary content with figures peppered in, as long as pictures/figures flow within, with or as part of text, vanilla L^AT_EX is fantastic.

One can relatively easily stretch the flow concept to more complex layouts introducing *even* and *odd* pages (the `book` class is one example) and flow rules based on them, but the next step, *bleeds*, combining page pairs into *spreads* as is often needed when designing image-oriented books is lacking. Full-bleed images/pages can be implemented manually, some more effort is needed to split something horizontally into a page spread, but doing so for whole book's worth of content is not practical – automating and experimenting with this process is how `photobook` began.

`photobook` extends the `book` class adding page layout types, bleeds and other global geometry configuration, introduces the *page* and *spread* as first-class elements into the document flow. These concepts are generalized as `cells`. A `cell` is similar to a figure, it can be placed within the document flow, but unlike a figure a `cell` can be aligned relative to a page, it can fill a page, a cell can even be horizontally split to fill several pages (how spreads are implemented).

On top of the `cell`, *page*, and *spread* concepts, `photobook` also builds a set of configurable high level macros and templates for common use cases like full bleed image spreads, foldouts, ... etc.

Usage

```
\documentclass[<options>]{photobook}
```

Options

Page geometry

```
blockwidth=<len> This is similar to what geometry does, but adds bleed support.
blockheight=<len>
bindingoffset=<len>
bleed=<len>
```

The diagram illustrates the page geometry with bleed and binding offset. It shows a page layout with dimensions for blockwidth, blockheight, bindingoffset, and bleed. The diagram includes labels for 'Page', 'textheight', and 'binding line'.

`flatfold=<len>` Sets the clearance set aside for a flat fold, used for foldouts (see: [Foldout page cells](#) section).

`pagefold=<fold>` Sets the default fold type.

Can be in or out.

`foldout=<fold-spec>` Sets the default fold specification (i.e. sets `\defaultfoldout`).

For more information see: [Foldout page cells](#) section.

layout

`layoutmode=<layout>` Set page layout mode.


`block`

`endpaper` `layoutmode=<option>`

`cover`


`jacket` `block` (default)

Basic page layout.



`endpaper:`

Endpaper layout.



`cover`

Book cover layout

```

          blockwidth      blockwidth
      <----->      <----->
      <-> coverboardgrow      <-> coverboardgrow
      <-> coverflap      . <-> coverflap
      . . .
      +-----++-----+
      | + - - - - - ++ - ++ - - - - - + | ---
      | . + - - - - - ++ - ++ - - - - - + . | --^ coverflap
      | . . . . . . . . . . . . . . | --^ coverboardgrow
      | . . . . . . . . . . . . . . | ^
      | . . . . . . . . . . . . . . | | blockheight
      | . . . . . . . . . . . . . . | |
      | . + - - - - - ++ - ++ - - - - - + . | v
      | + - - - - - - ++ - ++ - - - - - + | --v coverboardgrow
      +-----++-----+                --v coverflap
      ---
      . . .
      ^ . . ^ spinefold
      . .
      <---> spinewidth

```

coverboardgrow=<len>
coverflap=<len>
spinewidth=<len>
spinewidth=<len>

jacket

Dust jacket layout

```

      <---> jaketflap/jaketflapback      <---> jaketflap/jaketflapfront
      . . .
      . . .      blockwidth      blockwidth      . . .
      . . .      <----->      <----->      . . .
      . . .      <-> coverboardgrow      <-> coverboardgrow
      . . .
      +-----++-----+
      | .. + - - - - - ++ - ++ - - - - - + .. | ---
      | .. . . . . . . . . . . . . . . | --^ coverboardgrow
      | .. . . . . . . . . . . . . . . | ^
      | .. . . . . . . . . . . . . . . | | blockheight
      | .. . . . . . . . . . . . . . . | |
      | .. . . . . . . . . . . . . . . | v
      | .. + - - - - - ++ - ++ - - - - - + .. | --v coverboardgrow
      +-----++-----+                ---
      .. . . .
      ^ jacketwrap      . . .      ^ jacketwrap
      . . .
      ^ . . ^ spinefold
      . .
      <---> spinewidth

```

jacketwrap=<len>
jacketflap=<len>
jacketflapfront=<len>
jacketflapback=<len>

Note that for cover, endpaper, and jacket, `fancyhdr's \pagestyle{..}` is set to empty by default.

Image clearance

`clearimage=<len>` Distance from image to paper border (clearance) for full-page images.

this can be: - negative value set image bleed, - positive value set distance from paper edge to image.

Image block layout

`imageblockwidth=<len>` Image block size relative to text block.
`imageblockheight=<len>`
`imageblockoffsettop=<len>`

PDF Viewer layout

`pdfpagelayout=<mode>` Sets PDF page display mode.
 `SinglePage` Defaults to `TwoColumnLeft` for `layoutmode=block` and `SinglePage` for other modes.
 `OneColumn`
 `TwoColumnLeft` See: [hyperref's pdfpagelayout](#) for more options.
 `TwoColumnRight`
 `TwoPageLeft`
 `TwoPageRight`

Other options

`nofoldmarks` If given disable fold marks.
 This sets `\iffoldmarks` to false, otherwise it is set to true.

 `foldmarksizes=<len>` Sets the fold mark size (default: 6mm).

 `geometrynodefaults` let the user set geometry defaults.
 If this is not set `photobook` will override some user settings when initializing geometry.
 If set `photobook` will only set override:

```
paperwidth=\bleedblockwidth
paperheight=\bleedblockheight
bindingoffset=\bindingoffset
```

`roundprintedlengthsto=<num>` Number of digits to round printed lengths to (default: 1).
 This is a shorthand to `numprint's \nprouddigits{. .}`, use it to change values mid-document if needed.
 This is mostly used for `\GenerateTemplate`.

Packages

`photobook` adds and uses internally the following packages: [geometry](#), [kvoptions](#), [calc](#), [xargs](#), [ifthen](#), [iftex](#), [pgffor](#), [xint](#), [xinttools](#), [listofitems](#), [xkeyval](#), [etoolbox](#), [atbegshi](#), [hyperref](#), [eso-pic](#), [environ](#), [numprint](#), [trimclip](#), [xcolor](#), [colorspace](#), [graphicx](#), [adjustbox](#), [adjustbox](#), [fancyvrb](#), [tikz](#), [rotating](#), [fancyhdr](#), and [pdfpages](#).
Most of these packages can be used by the book author without explicitly importing them.

Globals

```
\layoutmode=<mode> Layout mode
\pdfpagelayout=<mode> Controls the default layout in the pdf viewer.
\spinewidth=<len> Spine width
\spinefold=<len> Spine fold width
\coverboardgrow=<len> Controls how much bigger the cover board is than the page block
\coverflap=<len> Cover flap
\jacketwrap=<len> Jacket configuration
\jacketflap=<len> Page block size
\jacketflapfront=<len> Page block size with bleeds
\jacketflapback=<len>
\blockwidth=<len> These are equivalent to \paperwidth and \paperheight but are independent of
\blockheight=<len> them...
\bleedblockwidth=<len> Original page block size
\bleedblockheight=<len>
\pageblockwidth=<len>
\pageblockheight=<len>
```

for the block layout these are the same as `\blockwidth` and `\blockheight` for other layouts these are the original page layout size while the `\blockwidth` are set tho the current layout visible size.

<code>\bleed=<len></code>	Page bleed size
<code>\bindingoffset=<len></code>	Binding offset
<code>\defaultfoldout=<fold-spec></code>	Set the default fold specification. This can be set via the <code>foldout</code> class option. For more information see: Foldout page cells section.
<code>\flatfold=<len></code>	Sets the amount of paper to account for a flat fold.
<code>\pagefold=<fold></code>	Default fold type. This defaults to <code>out</code> for <code>jacket</code> and <code>cover</code> and to <code>in</code> for other layouts.
<code>\foldmarkoffset=<len></code>	Sets the offset of fold marks from outside of page edge (default: <code>0.5\bleed</code>). Note that this can either be a command or a dimension.
<code>\foldmarksize=<len></code>	Sets fold marker size (vertical).
<code>\iffoldmarks</code>	Disable/enable fold marks. The default is true, to toggle on/off use <code>\foldmarkstrue</code> / <code>\foldmarksfalse</code> . This can be set globally via the <code>nofoldmarks</code> class option.
<code>\clearimage=<len></code>	Image clearance
<code>\imageblockwidth=<ratio></code>	Image block width relative to <code>\textwidth</code>
<code>\imageblockheight=<ratio></code>	Root page text width/height.
<code>\pagetextwidth=<len></code>	
<code>\pagetextheight=<len></code>	The ration by which the image is raised in <code>\ImagePage{..}</code> and derived templates.
<code>\imageblockoffsettop=<ratio></code>	Block caption clearance from edge of parent cell.
<code>\clearcaption=<len></code>	Used as default by <code>\captionblockcell{..}</code>
<code>\captioncellspacing=<len></code>	Block caption spacing from parent cell. Used as default by <code>\captionblockcell{..}</code>
<code>\captionclearpage=<len></code>	The distance between a caption block on a template page and page borders (defaults to: <code>\clearimage</code>). This is relevant only in page/spread templates.
<code>\cellparentwidth=<len></code>	Cell geometry.
<code>\cellparentheight=<len></code>	
<code>\cellwidth=<len></code>	These are set automatically by cells, thus it is not recommended to edit them manually.
<code>\cellheight=<len></code>	
<code>\celloffsetleft=<len></code>	For more details see the Cells section.
<code>\celloffsettop=<len></code>	Foldout geometry.
<code>\clearance=<len></code>	
<code>\clearfoldoutbinding=<len></code>	For more info see Foldout page cells section.
<code>\clearfoldoutfold=<len></code>	
<code>\clearfoldoutedge=<len></code>	

Initialization

<code>\InitPages</code>	Initialize page dimensions. This is not intended for direct use.
<code>\ReInitPages</code>	Reset and re-initialize page dimentions.

Generic commands

`\keywords{...}` Set pdf metadata keywords

`\keywords{<keywords>}`

`\subject{...}` Set pdf metadata subject

`\subject{<subject>}`

`\mindim{...}` Get min/max dimension.

`\maxdim{...}`

`\mindim{A}{B}`

`\maxdim{A}{B}`

`\emptypage{...}` Create an empty page.

`\emptypage`

`\emptypage[<style>]`

`<style>` is the style name as defined via `fancyhdr` (default: `empty`).

`\cleartoleftpage` Forces content to left page.

This is a companion to `\cleardoublepage`.

Environments and Cells

Generic

`page` Page environment.

This is mainly designed to wrap other cell environment described later.

Note that this may span more than one page if there is enough stuff packed in.

`leftpage`

EXPERIMENTAL

Cells

A cell environment is a box of specified size.

Cells can be both placed inline relative to other content or in an absolute location.

Note that absolute cells are placed relative to the page and currently can not be placed relative to other absolute cells (this might change in the future).

`\cellwidth=<len>`

`\cellheight=<len>`

`\cellparentwidth=<len>`


`\cellparentheight=<len>`

`\celloffsettop=<len>`

`\celloffsetleft=<len>`

`\clearance=<len>`

A cell defines a set of contextual lengths:



For absolutely positioned cells these define the cell offset from parent.

The bare page can be reasonably treated as a cell.

Initially, outside of any cells `\cellwidth`, `\cellparentwidth` and `\cellheight`, `\cellparentheight` are equal to `\paperwidth` and `\paperheight` respectively, and `\celloffsettop` and `\celloffsetleft` are set to 0pt.

Changing these is not recommended, it likely will not affect the current cell but can mess up nested cells.

`inlinecell` Create a basic inline cell.

```
inlinecell*
\begin{inlinecell}{<width>}{<height>} ... \end{inlinecell}

\begin{inlinecell}[<valign>]{<width>}{<height>} ... \end{inlinecell}
```

This will clip oversized content.

`inlinecell*` is like `inlinecell` but will not clip.

```
\begin{inlinecell*}{<width>}{<height>} ... \end{inlinecell*}

\begin{inlinecell*}[<valign>]{<width>}{<height>} ... \end{inlinecell*}
```

`<valign>` can be one of `t` (default) for top, `c` for center or `b` for bottom.

These are just like `minipage` but provide cell mechanics.

```
minipagecell EXPERIMENTAL
minipagecell* EXPERIMENTAL
zinlinecell
```

`zinlinecell*` Like `inlinecell` / `inlinecell*` but will take up zero space.

```
\begin{zinlinecell}{<width>}{<height>} ... \end{zinlinecell}

\begin{zinlinecell}[<valign>]{<width>}{<height>} ... \end{zinlinecell}
```

`cell` Create a basic absolutely positioned cell.

```
cell*
\begin{cell}{<left>, <top>}{<width>}{<height>} ... \end{cell}
```

Oversized content will be clipped.

`cell*` is just like `cell` but will not clip its content.

```
\begin{cell*}{<left>, <top>}{<width>}{<height>} ... \end{cell*}
```


`adjustcell` EXPERIMENTAL
`adjustcell*`

Save cells

`\savecell{...}` Create a saved cell.
`\gsavecell{...}` `\savecell{<name>}{<width>}{<height>}{ ... }`

This is similar to `\newsavebox{...}` and `\sbox{...}` but adds cell functionality.

`\gsavecell{...}` is the same as `\savecell{...}` but creates a global cell.

`\usecell{...}` Use part of a saved cell.
`\usecell*{...}` `\usecell{<name>}{<top>, <left>}{<width>}{<height>}`

This will clip the content to cell.

`\usecell*{...}` is similar to `\usecell{...}` but will not clip the cell content.

`\usecell*{<name>}{<top>, <left>}{<width>}{<height>}`

These are similar to `\usebox{...}`.

Cell macros

Cell macros require a cell environment to function correctly.

`topdown` Rotate cell content vertically, orienting it top-down or bottom-up.
`bottomup`

`\begin{topdown} ... \end{topdown}`
`\begin{bottomup} ... \end{bottomup}`

`cliptocell` Clip content to parent cell.
`\imagecell{...}` Place image in cell.

`\imagecell{<caption-cell>}{<image>}`
`\imagecell[<key>=<value>, ...]{<caption-cell>}{<image>}`
`\imagecell[fit]{...}{<image>}`
`\imagecell[fill]{...}{<image>}`

fit (default)	fill
<div style="border: 1px solid black; width: 80px; height: 40px; margin: auto; display: flex; align-items: center; justify-content: center;"> image </div>	<div style="border: 1px solid black; width: 80px; height: 40px; margin: auto; display: flex; align-items: center; justify-content: center;"> image </div>

Centering. The image will be centered by default.

`\imagecell{...}{<image>}`

`\imagecell[center]{}{<image>}`

Vertical alignment

`\imagecell[top]{}{<image>}`

`\imagecell[bottom]{}{<image>}`

top	center (default)	bottom
<pre> +-----+ image +-----+ +-----+ </pre>	<pre> +-----+ +-----+ image +-----+ +-----+ </pre>	<pre> +-----+ +-----+ image +-----+ </pre>

Horizontal alignment

`\imagecell[left]{}{<image>}`

`\imagecell[right]{}{<image>}`

left	center (default)	right
<pre> +-----+ image +-----+ </pre>	<pre> +-----+ image +-----+ </pre>	<pre> +-----+ image +-----+ </pre>

Horizontal and vertical alignment can be combined to control alignment of both vertical and horizontal images at the same time.

Image **clearance**. This sets the amount of clearance around an image (default: `0pt`).

`\imagecell[clearance=-4mm]{}{<image>}`

clearance > 0pt	clearance = 0pt (default)	clearance < 0pt
<pre> +-----v-----+ +-----+ > image < +-----+ +-----^-----+ </pre>	<pre> +-----+ +-----+ image +-----+ </pre>	<pre> +-----^-----+ ..+-----+.. < image >+-----+.. +-----v-----+ </pre>

```

+-----+ - - caption cell size
.
.
+-----+
| |
+-----+
..+-----+.. . +
. |.caption cell . | |
. | . . | . |
. | . . | . |
. | . . | . |
. | . . | . |
..+-----+.. . +
| |
+-----+

```

If `captionclearparent` is set, the `<caption-cell>` will fit into an intersection between the image area and the parent cell padded by `captionclearparent`.

To disable image list set:

`\captioncell{..}` Caption cell

`\captioncell[<position>]{<caption>}`

Default:

`\captioncell[over]{<caption>}`

`\captioncell[under]{<caption>}`

Horizontal alignment

`\captioncell[align=<mode>]{<caption>}`

+-----+	+-----+	+-----+
flushleft	center	flushright

Default:

`\captioncell{<caption>}`

`\captioncell[align=flushleft]{<caption>}`

`\captioncell[align=center]{<caption>}`

`\captioncell[align=flushright]{<caption>}`

Note that a caption cell does not take up any space in the parent cell so multiple captions can be used in combination with other elements.

Note that caption cells currently do not play well with other content in the same cell that takes up space, e.g. text, pictures, ...etc. Captions are mainly suited to play well with image cells.

`\vcaptioncell{..}` Vertical caption cell

(topdown)	(bottomup)
+-----+	+-----+
b l c r a	
e e e i f	
f f n g t	
o t t h e	e r
r e t r	r e t r
e r	o t t h e
	f f n g t
	e e e i f
	b l c r a
+-----+	+-----+

See samples for better illustration.

`\rcaptioncell{..}` EXPERIMENTAL

Upside-down caption cell.

`\captionblockcell{..}` Add caption into a box left/right of current cell.

`pagebleedcell` Like `page` but includes bleeds.

```

<-> bleed          <-> bleed

+-----+          + bleed
| + - - - - - + |  v
| .           . |
| .           . |
| . pagebleedcell . |
| .           . |
| .           . |
| + - - - - - + |  + bleed
+-----+          v

```

Note that as with `pagecell` this is not affected by `layoutmode`.

`textcell` EXPERIMENTAL

A cell taking up the page text block.

```
\begin{textcell}{<width>}{<height>} ... \end{textcell}
```

```

<-----> \textwidth

<-----> \pageblockwidth

+-----+ ^ \pageblockheight
|       | |
| +-----+ | ^ \textheight
| |       | |
| | textcell | |
| |       | |
| +-----+ | v
+-----+ v

```

Note that this is an inline cell and if something is on the page it may not be centered properly.

Foldout page cells

EXPERIMENTAL

A foldout is a special case cell that changes the page format.

In addition to cell lengths a foldout defines a set of additional lengths and lists within its context.

`\pagefoldpanels=<list>` Lists page folded panel widths and fold types respectively.

`\pagefoldpanelfolds=<list>` `pagefoldpanels` is set automatically for layouts other than `block` and for foldout pages, changing this can mess up fold markers and page cell placement.

`pagefoldpanelfolds` is generated when creating a foldout.

See: [listofitems](#) for list API.


`\foldoutwidth=<len>` Total foldout page width, calculated when a foldout page is created.

`foldout` Create 2 or more pages in foldout mode.

```
\begin{foldout}[<fold-spec>] ... \end{foldout}
```

<fold-spec> can be a number of folds, or contain one or more fold types (**in** or **out**), two or more panel widths (dimensions) or a sequence of both (i.e. dim fold dim ...) where missing widths are automatically calculated and missing folds are the same as the previous fold or the default if no folds are specified.


If not <fold-spec> is given, then the value of \defaultfoldout is used (default: 2).



A foldout always starts on the right/odd page and will always end on the left/even page.

If \foldoutpages{..} is called on an even page, an empty normal page will be created pushing the foldout to the right page of the spread. If an odd number of pages is created the set will be padded with an empty page before \foldoutpages{..} exits.

Foldout panel numbering



Formal <fold-spec> grammar:

```

<fold-spec> ::
  <count>
  | <fold>
  | <panels>
<panels> ::=
  <panel>
  | <panel> <panels>
<panel> ::=
  <width> <fold>
  | <width>
  | <fold>
<fold> ::=
  in | out

```

`\clearfoldoutbinding=<len>` Fold panel sizing for similar fold sequence:

```

\clearfoldoutedge=<len>
\clearfoldoutfold=<len>

```

```

\clearfoldoutedge <->
\clearfoldoutfold <->
<--> \clearfoldoutbinding

```

Note that `in` in fold sequence is drawn, `out` out is identical in sizing but reflected.

Fold panel sizing for dissimilar fold sequence:

```

\clearfoldoutedge <->
<--> \clearfoldoutbinding

```

`in` out is drawn, `out` it is the same but reflected.

The size of the paper fold is set by `\flatfold`.

`foldoutcell` Create a cell spanning one or more foldout panels.

`foldoutcell*`

```

\begin{foldoutcell}[<num>] ... \end{foldoutcell}

```

```

\begin{foldoutcell}[<from>-<to>] ... \end{foldoutcell}

```

If no arguments are given this will create a panel at `foldoutpanel` counter and increment it by one.

```

\begin{foldoutcell} ... \end{foldoutcell}

```

This will also auto-advance the page when all panels are filled.

Note that manual panel placement has no effect on the panel counter thus care must be taken when mixing manual and auto-advanced panels. Also note that `foldoutpanel`'s value is not maintained within manually placed panels and should be treated as undefined.

`foldoutcell*` is the same as the non-star version but creates cells including bleeds.

Neither version clips its content, to explicitly clip use the `cliptocell` environment.

These can only be used from within a `foldout` cell.

Multi-page cells

```
spreadtopages Spread cell into pages.
spreadtopages*
\usespreadpage{..}
\usespreadpage*{..}
```

The diagram illustrates the `spreadtopages` command. It shows a single cell containing the text "Oversized content cell..." which is then spread into multiple pages. The top part of the diagram shows the input cell, and the bottom part shows the output pages, each containing a portion of the original content.

`spreadtopages` creates a cell and spreads it into pages right away.

```
\begin{spreadtopages} .. \end{spreadtopages}
```

```
\begin{spreadtopages}[<page-count>] .. \end{spreadtopages}
```

`spreadtopages*` creates a named save cell only allowing the pages to be placed manually via `\usespreadpage{..}`.

```
\begin{spreadtopages*}{<name>} .. \end{spreadtopages*}
```

```
\begin{spreadtopages*}[<page-count>]{<name>} .. \end{spreadtopages*}
```

`\usespreadpage{..}` places a page from a saved cell.

```
\usespreadpage{<name>}
```

```
\usespreadpage[<page-num>]{<name>}
```

`\usespreadpage*{..}` is the same as the non-star version but will not use a `page` environment, enabling the user to populate the page with other elements.

Page numbers are 1-based.

Note that the cell created by `spreadtopages*` env is a normal save cell and can be manipulated via `\usecell{..}` and `\usecell*{..}`.

Endpaper cells

```
leftside
rightside
```

The diagram shows a two-column layout. The left column contains the text "leftside" and the right column contains the text "rightside".

Cover and dust jacket cells

frontcover Covers and dust jackets differ only in that covers do not usually have flaps.

backcover	backflap		spine/vspine		frontflap	
spine	.	backcover	.	frontcover	.	
vspine	v	v	v	v	v	
frontflap						
backflap						
		Back		Front		

Note that when typesetting a spine with both top-down and bottom-up text it is recommended to use `topdown/bottomup` in `zinlinecell`'s in a normal `spine` rather than using a `vspine` and trying to rotate part of the content.

Caption Templates

`\captionsize{..}` Defines the caption font.

Can be redefined to control caption font/style.

`\captionformat{..}` General caption format.

`\captionformat{<code>}`

This can be redefined to control the image caption.

Page Templates

This section contains a set of predefined configurable single-page templates.

Note that most page templates do not `\clearpage` before expanding, this enables one to prepend elements (like pdf comments), if clearing a page is required add `\clearpage` manually before the template.

Twaking

Most page/spread templates provide an ability to externally "tweak" some image proportions.

This is an alternative means to setting template properties, e.g:

```
\tweakimagescale{0.8}
\ImagePage{image}
```

Is equivalent to:

$$\backslash \text{ImagePage}[\text{scale}=0.8]\{\text{image}\}$$

Tweaks get reset after each template.

`\imagescale=<num>` Tweak next image templates scale/offsettop/offsetleft
`\imageoffsettop=<len>`
`\imageoffsetleft=<len>`

Note that `\imagescale` is not a length.

```
\edef\imagescale{<scale>}

\setlength\imageoffsettop{<len>}

\setlength\imageoffsetleft{<len>}
```

```
\tweakimagescale{..} Convenience commands
\tweakimageoffsettop{..} These provide a uniform interface for tweaking.
\tweakimageoffsetleft{..}
```

```
\tweakimagescale{<scale>}

\tweakimageoffsettop{<len>}

\tweakimageoffsetleft{<len>}
```

```
\resetimagetweaks{..} Reset tweaked values.
```

General interface

A templates provide a uniform interface consisting of several commands:

Base template command:

```
\<template-name>{<caption>}{<image>}

\<template-name>[<options>]{<caption>}{<image>}
```

`<options>` is the same as for `\imagecell{..}`.

Template-specific caption command:

```
\<template-name>Caption{<caption>}
```

This can be redefined to control typesetting the caption for all consecutive templates.

Reset template caption to default:

```
\reset<template-name>Caption
```

An equivalent to the non-star version but use the caption as-is:


```
\<template-name>*{<caption>}{<image>}

\<template-name>*[<options>]{<caption>}{<image>}
```

Note that though some template versions differ only in `<options>` defaults passed to `\imagecell{..}`, they are split to provide ability to configure the template defaults separately.

No bleed


```
\ImagePage{..} Basic image page
\ImagePageCaption{..}
\resetImagePageCaption
\ImagePage*{..}
```



Create an image page:

Note that `\ImagePage{..}` only supports tweaking **scale**, this is intentional and tweaking offset will mess up page alignment relative to other pages in a book.


```
\ImagePageClear{..}
\ImagePageClearCaption{..}
\resetImagePageClearCaption \ImagePageClear[<options>]{<caption>}{<image>}
\ImagePageClear*{..}
```



Default image clearance is set by `\clearimage` global length.


This respects `\bindingoffset`.

```
\ImagePageClear<D>{..} <D> can be one of T, B, L or R, for top, bottom, left and right respectively.
\ImagePageClear<D>Caption{..}
\resetImagePageClear<D>Caption
\ImagePageClear<D>*{..}
```



Partial bleed


```
\ImagePageFit{..} Fit image into page...
\ImagePageFitCaption{..}
\resetImagePageFitCaption \ImagePageFit[<options>]{<caption>}{<image>}
\ImagePageFit*{..}
```



Default image clearance is set by `\bleed` global length.


If centered image fits vertically this will account for `\bindingoffset`.

```
\ImagePageFit<D>{..} <D> can be one of T, B, L or R, for top, bottom, left and right respectively.
\ImagePageFit<D>Caption{..}
\resetImagePageFit<D>Caption
\ImagePageFit<D>*{..}
```



Full bleed

`\ImagePageFill{...}` Like `\ImagePage` but will fill page with image.
`\ImagePageFillCaption{...}`
`\resetImagePageFillCaption` `\ImagePageFill[<options>]{<caption>}{<image>}`
`\ImagePageFill*{...}`



Default image clearance is set by `\bleed` global length.

`\ImageHalfPageL{...}` Left half of image filling page with full bleed.
`\ImageHalfPageLCaption{...}`
`\resetImageHalfPageLCaption` `\imageleftspreadfullbleed[<vertical-offset>]{<caption>}{<image>}`
`\ImageHalfPageL*{...}`

A 10x10 grid of dots. A square region is defined by dashed lines. The region is labeled 'image' on the right and 'c' at the bottom right.

<code>\ImageHalfPageR{...}</code>	Right half of image filling page with full bleed.
<code>\ImageHalfPageRCaption{...}</code>	
<code>\resetImageHalfPageRCaption</code>	<code>\imagerightspreadfullbleed[<vertical-offset>]{<caption>}{<image>}</code>
<code>\ImageHalfPageR*{...}</code>	

A diagram showing a rectangular region defined by dashed lines. The region is labeled "image" on the left and "c" on the right. The region is filled with a grid of dots. The top and bottom edges are marked with "+" symbols.

Spread Templates

No bleed

```
\ImageSpread{..}
\ImageSpreadCaption{..}
\resetImageSpreadCaption
\ImageSpread*{..}
```

```

+-----+
| +-----+ |
| | . | |
| | . | |
| | . | |
| | image | |
| | . | |
| | . | |
| | . | |
| +-----+ |
+-----+


```

`\ImageSpread<D>{...}` <D> can be one of T, B, L or R, for top, bottom, left and right respectively.

`\ImageSpread<D>Caption{...}`

`\resetImageSpread<D>Caption`

`\ImageSpread<D>*{...}`




Partial bleed

```

\ImageSpreadFit{..}
\ImageSpreadFitCaption{..}
\resetImageSpreadFitCaption
\ImageSpreadFit*{..}


```



```


\ImageSpread<D>{..} Image spread aligned left (with bleed).
\ImageSpread<D>Caption{..}
\resetImageSpread<D>Caption \ImageSpread<D>[<options>]{<caption>}{<image>}
\ImageSpread<D>*{..}

```

Full bleed

```
\ImageSpreadFill{...} Image spread with full bleed.
\ImageSpreadFillCaption{...}
\resetImageSpreadFillCaption \ImageSpreadFill[<options>]{<caption>}{<image>}
\ImageSpreadFill*{...}
```



Meta Macros / Environments

These macros and environments are used internally to help define cells and templates and thus can be useful when extending the functionality of this class both when authoring styles and when creating user macros/templates.¹

¹Note that in code the relevant meta-macros are defined in the logical locations for each macro, i.e. before first use and at the start of the relevant context. This section in the reference is placed near the end so as to focus the user's attention on the main class interface, class internal architecture and extension API being secondary.

`\ResettableMacro{..}` Create a resettable command.

```
\ResettableMacro{<name>}{<code>}
```

```
\ResettableMacro{<name>}[<arg-count>]{<code>}
```

```
\ResettableMacro{<name>}[<arg-count>][<default>]{<code>}
```

This is similar to `\newcommand{..}` but will define two commands:

```
\<name>{..}
```

```
\reset<name>
```

`\<name>{..}` can be freely redefined or undefined by user.

`\reset<name>` will reset `\<name>{..}` to its original state.

`\CellContentOptions{..}`

EXPERIMENTAL

Define standard cell options.

`CellContent`

EXPERIMENTAL

`CellContent*` Standard cell content wrapper, used by `inlinecell`.

```
\begin{CellContent}[<parent-align>]{<name>} ... \end{CellContent}
```

```
\begin{CellContent*}[<parent-align>]{<name>}{<width>}{<height>} ... \end{CellContent}
```

The star version requires width/height to be manually passed while the non-star version will get the values from `\cellwidth` and `\cellheight` respectively.

`CellContent`

EXPERIMENTAL

`CellContent*` Like `CellContent` / `CellContent*` but will use `minipage` as the wrapper.

```
\begin{MinipageCellContent}[<parent-align>]{<name>} ... \end{MinipageCellContent}
```

```
\begin{MinipageCellContent*}[<parent-align>]{<name>}{<width>}{<height>} ... \end{MinipageCellContent}
```

`\ImagePageTemplate{..}`

```
\ImagePageTemplate{<name>}{<code>}
```

This will define two commands:

```
\<name>[<options>]{<caption>}{<code>}
```

```
\<name>*[<options>]{<caption>}{<code>}
```

`\<name>{..}` will use `\<name>Caption{..}` template command to typeset the image caption while `\<name>*{..}` will show the caption as-is.

Miscellaneous

`\PageInfo` Display basic paper / page / cell geometry.

`\GenerateTemplate{..}` Generate template page for current `layoutmode`.

```
\GenerateTemplate
```

Cell size can be printed in mm (default) or in any explicit unit supported by L^AT_EX.

```
\GenerateTemplate{<unit>}
```

This can be useful if one needs to make the cover/jacket/... in either a different software package or by hand.

This is a no-op for layoutmode=block.

```
\pdfboxesset{..}
```

```
\pdfboxesset[<bleed>]{<bleedblockwidth>}{<bleedblockheight>}
```

```
\pdfcommentcell{..}
```

 Add pdf comment as margin overlay.

```
\pdfcommentcell[<options>]{<comment>}
```

```
\pdfpagecount{..}
```

 Get pdf page count

```
\pdfpagecount{<file.pdf>}
```

```
\pdfspinewidth{..}
```

 Calculate spine thickness

```
\pdfspinewidth{<paper-thickness>}{<cover-thickness>}{<block-pdf>}
```

Why ASCII diagrams instead of normal graphics, you might ask? Well, for the same reason as photo-books in L^AT_EX – I liked the idea of it, the simplicity, and thought that it would be fun to see how far can I push things before it all falling apart on me, and... We are here, at the end, and it all is still here too :)